



# Titanium<sup>®</sup>- Homogeneous -65% ES-MU<sup>®</sup>

## **PRODUCT DESCRIPTIONS**

- Premium **Titanium™** homogeneous maintenance micro-grade (SGN 80) fertilizer with nitrogen and potash in 1:1 balanced ratio to promote healthy growth and stress resistance.
- This **Titanium™** product is white for greater visibility while spreading and breaks down easily with light irrigation to reduce mower pickup.
- 65 % of the nitrogen is provided by **ES-MU™** methylene urea. Nitrogen release through hydrolysis and the microbial degradation of varying length urea polymer chains ensures consistency and longevity.
- All the potassium is derived from sulphate of potash, a safe and natural source of potassium and sulphur.

## **PRODUCT BENEFITS**

- Titanium<sup>™</sup> homogeneous fertilizers are the top-of-the-line products formulated to optimize nutrient application to your turf. Titanium<sup>™</sup> technology is designed to make granular fertilization as uniform as possible; each granule contains all of the nutrients essential to healthy growth.
- Micro-grade homogeneous fertilizer provides an even distribution of nutrients at lower rates for optimum results.
- ES-MU<sup>™</sup> methylene urea slow-release nitrogen is a trusted technology that provides gradual and consistent release. Exceptional 12-16 week longevity allows for effective feeding all season long.

## **PRODUCT CHARACTERISTICS**

Product Code: C110084

Product Type: Homogeneous fertilizer for greens and tees

- Size: Micro (SGN 80)
- Net Weight: 20 kg
  - Density: 1 008 kg/m<sup>3</sup> (63 lb/pi<sup>3</sup>)

Coverage: 20 940 ft<sup>2</sup> at 2,1 lb/1000 ft<sup>2</sup>

13 960 ft<sup>2</sup> at 3,2 lb/1000 ft<sup>2</sup>

## GUARANTEED MINIMUM ANALYSIS %

Total Nitrogen (N)
Soluble Potash (K <sub>2</sub> O)

\* 10.5% Slowly available nitrogen from methylene urea.

### INGREDIENTS

Methylene urea, Urea, Potassium sulphate, Calcium sulphate.







www.envirosol.ca

# Titanium<sup>®</sup> - 65% ES-MU<sup>®</sup>

### **APPLICATION RATES**

Bag kg	Application Rate	Application Rate		Nutrients supplied /100 m <sup>2</sup> (lb/1,000 †		Area Covered m <sup>2</sup> (ft <sup>2</sup> )	Bags required per hectare (acre)
(lb)	kg/100 m <sup>2</sup> (lb/1,000 ft <sup>2</sup> )	kg/ha (Ib/acre)	N	P <sub>2</sub> O <sub>5</sub>	K <sub>2</sub> O		
20 (44)	1.0 (2.1)	103 (92)	0.20 (0.40)	-	0.20 (0.40)	1,950 (20,940)	5.1 (2.1)
	1.5 (3.2)	154 (138)	0.29 (0.60)	-	0.29 (0.60)	1,300 (13,960)	7.7 (3.1)

### **DIRECTIONS FOR USE**

- Read the entire label before use. Apply only as directed.
- Apply only to dry foliage.
- IMPORTANT: It is recommended to apply fertilizers in the early morning. Water in after application, especially during periods of high temperatures (28°C or above). Avoid applying fertilizer to drought-stressed turf. If turf is under drought stress, irrigate before fertilizer application.
- Irrigating after application will accelerate initial green-up and will aid in the movement of fertilizer granules into the turf canopy.
- Apply after mowing to prevent particle pick-up by mowing equipment.



#### SUGGESTED SPREADER SETTINGS

To provide proper distribution, calibrate spreader before application.

Broadcast Spreader	Ground speed km/h (mph)	Application width m (ft)	Rate 1.0 kg/100 m <sup>2</sup> (2.1 lb/1000 ft <sup>2</sup> )	Rate 1.5 kg/100 m <sup>2</sup> (3.2 lb/1000 ft <sup>2</sup> )
Accupro 2000	5 (3)	2.5 (8)	F ½	G ½
Scotts R-8A	5 (3)	2.5 (8)	G	н
Prizelawn BF-1 / CBR III	5 (3)	2.5 (8)	G	н
Earthway Rotary	5 (3)	2.5 (8)	9	10
Lesco (Letter / Number)	5 (3)	2.5 (8)	C/8	C ½ / 9
Cyclone / Spyker	5 (3)	2.5 (8)	3.5	3.75

Note: All calibration starting points given on back are for wheel-to-wheel coverage (100% overlap). The spreader settings should only be used for calibration starting points as age, wear and speed of spreader will impact actual applied rate.

#### PRECAUTIONS

KEEP OUT OF REACH OF CHILDREN. Harmful if swallowed. Do not inhale. Fertilizer may cause irritation of eyes, nose, throat and skin. In case of contact with eyes, flush with plenty of water; seek medical attention.

Titanium<sup>™</sup> and ES-MU<sup>™</sup> are trademarks of Enviro-Sol. Rev1403

Ontario and Western Canada : 1-877-785-1098 Quebec and Maritimes : 1-800-363-9436



www.envirosol.ca