

24

4

12



Regular
SGN 225



65% ES-COTE™

PRODUCT DESCRIPTION

- 65% of the nitrogen is derived from **ES-COTE™** polymer-coated, sulphur-coated urea. **ES-COTE™** slow-release nitrogen provides extended feeding.

PRODUCT BENEFITS

- ES-COTE™** slow-release fertilizer uses breakthrough technology to provide a unique coating that allows gradual and consistent nutrient release delivering up to 8 weeks of continuous feeding.
- The release of nitrogen, depending on soil moisture conditions occurs predictably over time, allowing you to plan your applications according to the needs of the plant.
- The coating on **ES-COTE™** will also protect against nitrogen leaching losses during periods of intensive rainfall.

PRODUCT CHARACTERISTICS

- Product Code:** R540456
- Product Type:** Professional Lawn Fertilizer
- Size:** Regular (SGN 225)
- Format:** 25 kg
- Density:** 977 kg/m³ (61 lb/ft³)
- Coverage:** 17,640 ft² @ 3.1 lb/1,000 ft²
13,230 ft² @ 4.2 lb/1,000 ft²

GUARANTEED MINIMUM ANALYSIS

	%
Total Nitrogen (N)	24.00
14.5% Nitrogen from Polymer-coated, sulphur-coated urea	
7.9% Urea Nitrogen	
1.6% Ammonia nitrogen	
Phosphoric Acid (P ₂ O ₅)	4.00
Soluble Potash (K ₂ O)	12.00
Sulphur (S) actual	1.4

INGREDIENTS

Urea, Polymer-coated, sulphur-coated urea, Muriate of potash, Ammonium phosphate.



APPLICATION RATES

Bag kg (lb)	Application Rates kg/100 m ² (lb/1,000 ft ²)	Nutrition Supplied kg/100 m ² (lb/1,000 ft ²)			Area Treated m ² (ft ²)
		N	P ₂ O ₅	K ₂ O	
25 (55)	1.5 (3.1)	0.37 (0.75)	0.06 (0.13)	0.18 (0.38)	1,640 (17,640)
	2.0 (4.1)	0.49 (1.0)	0.08 (0.17)	0.24 (0.50)	1,230 (13,230)

DIRECTIONS FOR USE

- Read the entire label before use. Apply only as directed.
- Apply only to dry foliage.
- **IMPORTANT:** It is recommended to apply fertilizers in the early morning. Irrigate after application, especially during periods of high temperatures (28°C or above). Avoid applying fertilizer to drought-stressed turf. If turf is under drought stress, irrigate before fertilizer application.
- Irrigating after application will accelerate initial green-up and will aid in the movement of fertilizer granules into the turf canopy.
- Apply after mowing to prevent particle pick-up by mowing equipment. To further reduce particle pick, do not collect clippings for one mowing after application.

Format

25 kg

SUGGESTED SPREADER SETTINGS

To provide proper distribution, calibrate spreader before application.

Rotary Spreader	Ground Speed km/h (mph)	Width of Coverage m (ft)	Rate 1.5 kg/100 m ² (3.1 lb/1,000 ft ²)	Rate 2.0 kg/100 m ² (4.1 lb/1,000 ft ²)
Accupro 2000	5 (3)	3.5 (12)	H ½	I ½
Scotts R-8A	5 (3)	3.5 (12)	I	J
Prizelawn BF-1 / CBR III	5 (3)	3.5 (12)	I	I ½
Earthway Rotary	5 (3)	3.5 (12)	13	14
Lesco (Letter / Numeric)	5 (3)	3.5 (12)	D / 10	D ½ / 11
Cyclone / Spyker	5 (3)	3.5 (12)	4	4.25
Lely Models WTR, WFR, HR, 1250 (PTO at 450 rpm)	7 (4.5)	12 (40)	4.75	5.5
Vicon (03 Series - Standard Spout)	7 (4.5)	12 (40)	19	22

Note: All calibration starting points given on back are for wheel-to-wheel coverage (100% overlap). The spreader settings should only be used for calibration starting points as age, wear and speed of spreader will impact actual applied rate.

PRECAUTIONS

KEEP OUT OF REACH OF CHILDREN. Harmful if swallowed. Do not inhale. The fertilizer may cause irritation of eyes, nose, throat and skin. In case of contact with eyes, rinse thoroughly with water and consult a physician if symptoms occur. Keep out of reach of animals.

ES-COTE is a trademark of Enviro-Sol.
Rev1412

Québec and Maritimes : **1 800 363 9436** Ontario and Western Canada : **1 877-785-1098**

www.envirosol.ca

EnviroSol
THE FERTILIZER SOLUTION