



Calcitic Lime

PRODUCT DESCRIPTIONS

- Used to increase the pH of acidic soils.
- Contains 36% calcium

PRODUCT BENEFITS

- The role of calcium is to promote cell growth and strengthen cell walls. Calcium makes the plant more tolerant of environmental stresses.

PRODUCT CHARACTERISTICS

- Product Code:** R526099
- Product Type:** Amendment to adjust soil pH
- Size:** Reg (SGN 225)
- Net Weight:** 25 kg
- Density:** 1,104 kg/m³ (69 lb/ft³) (Regular)
- Coverage:** 11,000 ft² at 5 lb/1,000 ft²
5,500 ft² at 10 lb/1,000ft²

GUARANTEED MINIMUM ANALYSIS

	%
Calcium (Ca)	36.00
Calcium Carbonate (CaCO ₃)	90.00
Magnesium (Mg)	0.50
Magnesium Carbonate (MgCO ₃)	1.70
Neutralizing Value (Calcium carbonate equivalent)	92.00

Particle sizing

Sieve	% Passing
2 mm	100.00
0.15 mm	95.00

INGREDIENTS

Calcium carbonate.

Calcitic Lime

Ca

APPLICATION RATES

Bag kg (lb)	Application Rate kg/100 m ² (lb/1,000 ft ²)	Application Rate kg/ha (lb/acre)	Nutrients supplied kg/100 m ² (lb/1,000 ft ²)			Area Covered m ² (ft ²)	Bags required per hectare (acre)
			Ca	-	-		
25 (55)	2.5 (5.0)	244 (218)	0.8 (1.8)	-	-	1,000 (11,000)	9.8 (4.0)
	5.0 (10.0)	488 (435)	1.8 (3.6)	-	-	500 (5,500)	19.5 (7.9)

DIRECTIONS FOR USE

- Read directions before using. Apply only as recommended.
- Follow soil test recommendations for application rates regarding the adjustment of soil pH and calcium levels.
- For new construction, application rate can be higher if the calcitic lime is mechanically incorporated into the soil.
- Irrigating after application will aid in the movement of fertilizer granules into the turf canopy.

Net Weight

25 kg

SUGGESTED SPREADER SETTINGS

Rotary Spreader	Ground Speed km/h (mph)	Width of Application m (pi)	Rate 2.5 kg/100 m ² (5 lb/1000 ft ²)	Rate 5 kg/100 m ² (10 lb/1000 ft ²)
Accupro 2000	5 (3)	3.5 (12)	G ½	H ½
Scotts R-8A	5 (3)	3.5 (12)	H	I
Prizelawn BF-1 / CBR III	5 (3)	3.5 (12)	H	J
Earthway Rotary	5 (3)	3.5 (12)	12.5	14.5
Lesco (Letter / Numeric)	5 (3)	3.5 (12)	D / 10	D ½ / 11
Cyclone / Spyrer	5 (3)	3.5 (12)	3.75	4
Lely Models WTR, WFR, HR, 1250 (PTO at 450 rpm)	7 (4.5)	12 (40)	5.75	7
Vicon (03 Series - Standard Spout)	7 (4.5)	12 (40)	24	28

Note: All calibration starting points given on back are for wheel-to-wheel coverage (100% overlap). The spreader settings should only be used for calibration starting points as age, wear and speed of spreader will impact actual applied rate.

PRECAUTIONS

KEEP OUT OF REACH OF CHILDREN. Harmful if swallowed. Do not inhale. Fertilizer may cause irritation of eyes, nose, throat and skin. In case of contact with eyes, flush with plenty of water; seek medical attention.

Rev1410

Ontario and Western Canada : 1-877-785-1098 Quebec and Maritimes : 1-800-363-9436

www.envirosol.ca

EnviroSol
THE FERTILIZER SOLUTION